

RV1 OVER THE PIPE HOSE




RV1 hose can slip over piping outer diameters for a sleeve fit. It is available in a wide range of diameters to both fit over pipe, and for other purposes. It is constructed of oil resistant nitrile rubber and polyester tire cord reinforcement. Meets SAEJ2006.

-40F to 210F. Not for steam service.

QTY	INNER DIA	OAL	FITTINGS	OUTER DIA	PRESSURE	BEND RADIUS	WEIGHT
	(in)	(in)		(in)	(psi)	(in)	(lbs/ft)
	7/8			1.28	250	-	0.51
	1			1.41	250	-	0.56
	1 1/8			1.54	250	-	0.63
	1 1/4			1.66	225	-	0.69
	1 3/8			1.78	220	-	0.75
	1 1/2			1.96	200	-	0.89
	1 5/8			2.08	185	-	0.96
	1 3/4			2.26	175	-	1.11
	1 7/8			2.38	160	-	1.19
	2			2.50	150	-	1.25
	2 1/8			2.63	150	-	1.31
	2 1/4			2.76	140	-	1.38
	2 3/8			2.80	250	-	1.33
	2 1/2			3.07	250	-	1.8
	2 5/8			3.13	225	-	1.75
	2 3/4			3.31	220	-	1.98
	2 7/8			3.43	220	-	2.05
	3			3.54	210	-	2.07
	3 1/8			3.66	200	-	2.16
	3 1/4			3.80	190	-	2.29
	3 1/2			4.05	180	-	2.44
	4			4.60	150	-	3.11
	4 1/2			5.18	140	-	3.85
	5			5.69	130	-	4.31
	5 1/2			6.21	120	-	4.81
	6			6.74	110	-	5.48
	6 5/8			7.37	100	-	6.02
	8 5/8			9.38	100	-	7.05
	10 3/4			11.50	100	-	7.9
	12 3/4			13.50	100	-	9.18

NOTES: THE HOSE IS RATED FROM -40F TO 210F.

CUSTOMER _____ PROJECT _____ ENGINEER _____ CONTRACTOR _____ CERTIFICATION _____	 "Flexible Piping Solutions"
	MODEL: RV1
	DRAWN BY: PDB 1/1/04
	OVER THE PIPE HOSE