

TD1 THERMOPLASTIC RUBBER COATED DUCT HOSE




The Model TD1 is a thermoplastic rubber hose, which has the strength of plastic and the durability of rubber. It is very well suited to most lower pressure industrial duct jobs, as well as light material handling and more. This versatile hose has excellent resistance to many commonly used industrial fluids, and has good abrasion, puncture, and weathering resistance. Also available with integral external wear strip.

Normally clamped to fittings or equipment with bridge clamps. Temperature range is -60F to 275F.

QTY	HOSE DIA	OAL	FITTINGS	PRESSURE	VACUUM	BEND RADIUS	WEIGHT
	(in)	(ft)		(psi)	(in Hg)	(in)	(lbs/in)
	1 1/4			28	29	1 1/2	0.11
	1 1/2			24	29	1 3/4	0.22
	1 3/4			22	29	2	0.23
	2			17	29	3 1/2	0.24
	3			10	28	4 1/4	0.32
	4			10	25	6 1/2	0.5
	5			9	15	8	0.63
	6			8	11.5	8 3/4	0.85
	7			7	10	10 1/2	0.95
	8			6	5.5	12	1.2
	10			4	5	12 1/2	1.63
	12			4	4	13 3/4	1.9
	14			2	2	18	1.87
	16			2	2	21	3.19
	18			2	2	21 1/2	3.36
	20			1	2	25 1/2	3.63
	24			1	1	36	3.81

NOTES: THE HOSE IS RATED FOR -60F TO 275F..

CUSTOMER _____ PROJECT _____ ENGINEER _____ CONTRACTOR _____ CERTIFICATION _____	 "Flexible Piping Solutions"				
	<table border="1" style="width: 100%;"> <tr> <td style="width: 50%;">MODEL:</td> <td style="width: 50%; text-align: center;">TD1</td> </tr> <tr> <td style="width: 50%;">DRAWN BY: PDB 1/1/04</td> <td style="width: 50%; text-align: center;">THEMOPLASTIC RUBBER COATED DUCT</td> </tr> </table>	MODEL:	TD1	DRAWN BY: PDB 1/1/04	THEMOPLASTIC RUBBER COATED DUCT
MODEL:	TD1				
DRAWN BY: PDB 1/1/04	THEMOPLASTIC RUBBER COATED DUCT				