


PT2 CLEAR PVC TUBING



PT2 is a crystal clear unreinforced PVC tubing with a smooth interior. Their is a mirror-smooth finish to provide excellent flow characteristics. Applications are varied, and include a variety of weak chemicals and gases, including food products, and is easily flushed and cleaned. FDA, USDA, 3A and NSF grade. 25F to 150F.

QTY	INNER DIA	OAL	FITTINGS	OUTER DIA	PRESSURE	COIL LENGTH
	(in)	(in)		(in)	(psi)	(feet)
	1/16			1/8	65	100
	1/8			1/4	65	100
	3/16			5/16	55	100
	1/4			3/8	50	100
	1/4			7/16	60	100
	1/4			1/2	70	100
	5/16			7/16	40	100
	5/16			1/2	50	100
	3/8			1/2	35	100
	3/8			9/16	50	100
	3/8			5/8	60	100
	7/16			9/16	40	100
	1/2			5/8	30	100
	1/2			11/16	40	100
	1/2			3/4	45	100
	5/8			7/8	40	100
	3/4			1	35	100
	7/8			1 1/8	30	100
	1			1 1/4	25	100
	1 1/4			1 1/2	25	50
	1 1/4			1 5/8	35	50
	1 1/2			1 7/8	30	50
	1 1/2			2	35	50
	2			2 1/2	30	50

NOTES: *THE HOSE IS RATED FOR 25 TO 150 DEG F. HIGHER TEMPERATURES THAN 70F AFFECT PRES. RATING.

CUSTOMER _____ PROJECT _____ ENGINEER _____ CONTRACTOR _____ CERTIFICATION _____	 "Flexible Piping Solutions"				
	<table border="1" style="width: 100%;"> <tr> <td style="width: 50%;">MODEL:</td> <td style="width: 50%; text-align: center;">PT2</td> </tr> <tr> <td>DRAWN BY: PDB 8/04</td> <td style="text-align: center;">CLEAR PVC</td> </tr> </table>	MODEL:	PT2	DRAWN BY: PDB 8/04	CLEAR PVC
MODEL:	PT2				
DRAWN BY: PDB 8/04	CLEAR PVC				